



Permit Weight Table 1

(REVISED 08-2002)

The following exceptions apply to the table of weights shown below:

Exception 1: Two consecutive tandem axles may weigh up to 34,000 pounds each if:

Minimum Axle Spacing Required	Interstate Highways	Non-Interstate Highways
30 feet or more	Permit Required	No Permit Required
36 feet or more	No Permit Required	No Permit Required

Exception 2: A group of four axles consisting of a set of tandem axles and two axles spaced nine feet or more apart may have a loaded weight of more than 65,500 pounds and up to 70,000 pounds if:

Minimum Axle Spacing Required	Interstate Highways	Non-Interstate Highways
35 feet or more	Permit Required	No Permit Required

- Minimum axle spacing is the distance between the first and last axle of any group shown above.

Wheelbase In Feet * ▼	Number of Axles						Wheelbase In Feet * ▼	Number of Axles					
	2	3	4	5	6	7 Or More		2	3	4	5	6	7 Or More
4	34,000	34,000	34,000	34,000	34,000	34,000	31	40,000	59,000	62,500	67,500	72,500	78,000
5	34,000	34,000	34,000	34,000	34,000	34,000	32	40,000	60,000	63,500	68,000	73,000	78,500
6	34,000	34,000	34,000	34,000	34,000	34,000	33	40,000	60,000	64,000	68,500	74,000	79,000
7	34,000	34,000	34,000	34,000	34,000	34,000	34	40,000	60,000	64,500	69,000	74,500	80,000
8 & less	34,000	34,000	34,000	34,000	34,000	34,000	35	40,000	60,000	65,500	70,000	75,000	80,000
Over 8	38,000	42,000	42,000	42,000	42,000	42,000	36	40,000	60,000	66,000	70,500	75,500	80,000
9	39,000	42,500	42,500	42,500	42,500	42,500	37	40,000	60,000	66,500	71,000	76,000	80,000
10	40,000	43,500	43,500	43,500	43,500	43,500	38	40,000	60,000	67,500	71,500	77,000	80,000
11	40,000	44,000	44,000	44,000	44,000	44,000	39	40,000	60,000	68,000	72,500	77,500	80,000
12	40,000	45,000	50,000	50,000	50,000	50,000	40	40,000	60,000	68,500	73,000	78,000	80,000
13	40,000	45,500	50,500	50,500	50,500	50,500	41	40,000	60,000	69,500	73,500	78,500	80,000
14	40,000	46,500	51,500	51,500	51,500	51,500	42	40,000	60,000	70,000	74,000	79,000	80,000
15	40,000	47,000	52,000	52,000	52,000	52,000	43	40,000	60,000	70,500	75,000	80,000	80,000
16	40,000	48,000	52,500	58,000	58,000	58,000	44	40,000	60,000	71,500	75,500	80,000	80,000
17	40,000	48,500	53,500	58,500	58,500	58,500	45	40,000	60,000	72,000	76,000	80,000	80,000
18	40,000	49,500	54,000	59,000	59,000	59,000	46	40,000	60,000	72,500	76,500	80,000	80,000
19	40,000	50,000	54,500	60,000	60,000	60,000	47	40,000	60,000	73,500	77,500	80,000	80,000
20	40,000	51,000	55,500	60,500	66,000	66,000	48	40,000	60,000	74,000	78,000	80,000	80,000
21	40,000	51,500	56,000	61,000	66,500	66,500	49	40,000	60,000	74,500	78,500	80,000	80,000
22	40,000	52,500	56,500	61,500	67,000	67,000	50	40,000	60,000	75,500	79,000	80,000	80,000
23	40,000	53,000	57,500	62,500	68,000	68,000	51	40,000	60,000	76,000	80,000	80,000	80,000
24	40,000	54,000	58,000	63,000	68,500	74,000	52	40,000	60,000	76,500	80,000	80,000	80,000
25	40,000	54,500	58,500	63,500	69,000	74,500	53	40,000	60,000	77,500	80,000	80,000	80,000
26	40,000	55,500	59,500	64,000	69,500	75,000	54	40,000	60,000	78,000	80,000	80,000	80,000
27	40,000	56,000	60,000	65,000	70,000	75,500	55	40,000	60,000	78,500	80,000	80,000	80,000
28	40,000	57,000	60,500	65,500	71,000	76,500	56	40,000	60,000	79,500	80,000	80,000	80,000
29	40,000	57,500	61,500	66,000	71,500	77,000	57 or more	40,000	60,000	80,000	80,000	80,000	80,000
30	40,000	58,500	62,000	66,500	72,000	77,500							

The loaded weight of any group of axles, vehicle, or combination of vehicles shall not exceed that specified in the table of weights shown above or any of the following:

- The manufacturer's side wall tire rating but not to exceed 600 pounds per inch of tire width.
- 600 pounds per inch of tire width.
- 20,000 pounds on any one axle, including any one axle of a group of axles.
- 34,000 pounds on any tandem axle.
- The sum of the permissible axle, tandem axle, or group of axle weights shown above, whichever is less.

Note exceptions 1 and 2 above.